

HIGH DENSITY DESIGN FOR GREATER FLEXIBILITY

The OL5KRTHD and OL6KRTHD pack maximum power, functionality, and efficiency into a compact design, compared to similar 3U and 4U competitive models. The combined power and features allow IT professionals flexibility and room to grow.



DOUBLE-CONVERSION TOPOLOGY

Near perfect double-conversion power safeguards mission-critical servers, applications, and network equipment.



BATTERY EQUALIZATION TECHNOLOGY

Advanced charging process that maintains the voltages of the batteries at the same level to increase battery life.



EASY BATTERY REPLACEMENT

Front panel features side latch for toolless removal. Single faceplate screw makes battery replacement easy.



FULL COLOR MATRIX LCD CONTROL PANEL

Auto-rotating, multi-function color LCD screen. Color display provides ups status, controls, event logs, and diagnostics.

PERFECT POWER. SMALL SPACE.

First 5k and 6kVA High-Density UPS Systems with 2U Design

Keep business running smoothly with this space-saving UPS design. Compact components and circuitry; 3U/4U power in 2U server rack space. Maximum efficiency and capacity output with a Power Factor rating (PF) of 1.



USER-FRIENDLY LCD SCREEN

Fully Adjustable, Color Coded Display











HIGH DENSITY UPS SYSTEMS

MODEL	VA	WATTS	OUTLETS	WARRANTY
OL5KRTHD	5000	5000	2 x NEMA L6-20R, 2 x NEMA L6-30R	Three-Year
OL6KRTHD	6000	6000	2 x NEMA L6-20R, 2 x NEMA L6-30R	Three-Year

EXTENDED BATTERY MODULES

MODEL	VOLTAGE	AMPERAGE	RECHARGE TIME	WARRANTY	UPS COMPATIBILITY
BP144VL2U01	144	55	4 hours	Three-Year	OL5KRTHD, OL6KRTHD

